



Ski Skins Tail Clip Kit

—SKI SKIN WIDTH—



-110mm & UNDER



+111mm & OVER

KIT INCLUDES

- (6) 3/16D x 5/16L x 3/8H Rivets
- (2) Stainless Steel Tail Clips
- (2) Sticker Templates
- (2) Tail Attachments
- (2) 15" Skin Tail Straps

-110mm Pair Weight: 3.45oz/98g

+111mm Pair Weight: 3.6oz/102g



Maximum Distance from Skin Tail
to Ski Tail : 12 1/4"/31cm



*If the distance between your skin tail and
ski tail exceeds 12 1/4"/31cm this kit will not fit.



Spare Skin Tail Straps available
in both 10" and 15" lengths.



voile.com

REQUIRED TOOLS

Pliers & Phillips Screwdriver
Butane Torch / Framing Nail or Screw
Razor Knife/Box Cutter
Ball-Peen Hammer



Before you do anything, it is important to determine your desired skin length by test fitting the tail attachments to your skis. You must allow enough room for the strap to properly apply tension to the tail clip. If you intend on using one pair of skins for multiple skis, before cutting, check to make sure the tail clip kit will properly fit both.

1. Cut out the two sticker templates and place them on the each skin on the plush side. Justify the sticker to the straight tail edge of your skin. Press firmly. **DO NOT STICK TO THE GLUE SIDE.**

2. In a well ventilated area, holding the nail with a pair of pliers, heat with a butane torch until it is red-hot. Center the heated nail over the middle hole and slowly force through the template and skin. Once the nail is through both the template and skin, slowly widen the hole in a circular motion. Repeat this for the two outside holes.

3. With the template still affixed to the skin, cut out the square notch with a razor knife. Remove the template and gently cut off any excess material that has melted to either side of the skin. (Figure 1)

4. Test fit the tail attachment, paying particular attention to the two rectangle cut aways. The larger rectangle should face the glue side of the skin. Now test fit the rivets. If the rivets are impeded by any skin material, repeat step two until each rivet can slide in and out easily. If you cannot align the holes easily, gently cut a small amount off of the tail.

5. On a hard surface, starting with the center rivet gently begin to open the end of the rivet with the phillips screwdriver. Rotate the screwdriver 45° and repeat. Then gently round the ends of the rivet with a ball-peen side of the hammer. **TAKE YOUR TIME.** Repeat this for the other two rivets. (Figure 2 & 3)

6. Now flip the skin over and with the head face of your hammer, begin to gently hammer the head of each rivet until it clinches the tail attachment. (Figures 4) You may need to rotate the rivet slightly so that it clinches all sides properly.

7. Slide the strap through the larger rectangle cutaway until it snaps into place. The Voilé logo should face out, or towards the plush side of the skin. (Figure 5)

8. Slide on the tail clip and test fit the skins to your skis. There should be enough stretch in the strap to allow the tail clip to properly apply enough tension to secure the tail clip in place. (Figure 6)

Voilé is not responsible for improper installation, misuse or abuse of this product. This product is warranted by the manufacturer against any defects in materials or workmanship for a period of one year. Warranty service and replacement parts are available directly from Voilé.

